

ArticFlex Straight Cable Assemblies



- Heavy duty, multi-strand copper conductors
- Superior Flexibility and durability
- Flexible in temperatures to -85°F (-65°C)
- Rugged abrasion resistant jacket is unaffected by gasoline, diesel fuel and commonly encountered chemicals
- Available with spring guards or the popular Tectran **WeatherSeal**
- Durable Buffalo die-cast plugs are standard



Length	Conductors / Gauge	Jacket Color	Connectors	Part No. with Spring Guard	Stock Code	Part No. with Weather Seal	Stock Code	ABS
8'	4/12 - 2/10 - 1/8	Green	2 - SAE-Primary	—	—	7AAB082MW	37027	Yes
10'	4/12 - 2/10 - 1/8	Green	2 - SAE-Primary	7AAB102MG	37028	7AAB102MW	37029	Yes
12'	4/12 - 2/10 - 1/8	Green	2 - SAE-Primary	7AAB122MG	37030	7AAB122MW	37031	Yes
15'	4/12 - 2/10 - 1/8	Green	2 - SAE-Primary	7AAB152MG	37032	7AAB152MW	37033	Yes
20'	4/12 - 2/10 - 1/8	Green	2 - SAE-Primary	—	—	7AAB202MW	37034	Yes
10'	4/12 - 2/10 - 1/8	Green	2 - Poly SAE-Primary	7AAB102PG	37274	—	—	Yes
12'	4/12 - 2/10 - 1/8	Green	2 - Poly SAE-Primary	7AAB122PG	37260	—	—	Yes
15'	4/12 - 2/10 - 1/8	Green	2 - Poly SAE-Primary	7AAB152PG	37269	—	—	Yes
20'	4/12 - 2/10 - 1/8	Green	2 - Poly SAE-Primary	7AAB202PG	37275	—	—	Yes
10'	4/12 - 2/10 - 1/8	Yellow	2 - SAE-Aux	—	—	7AEB102EW	37036	Yes
12'	4/12 - 2/10 - 1/8	Yellow	2 - SAE-Aux	7AEB122EG	37037	7AEB122EW	37038	Yes
15'	4/12 - 2/10 - 1/8	Yellow	2 - SAE-Aux	—	—	7AEB152EW	37079	Yes
20'	4/12 - 2/10 - 1/8	Yellow	2 - SAE-Aux	—	—	7AEB202EW	37041	Yes
10'	6/12 - 1/10	Black	2 - SAE-Primary	—	—	7SAB102MW	37218	No
12'	6/12 - 1/10	Black	2 - SAE-Primary	7SAB122MG	37219	7SAB122MW	37220	No
15'	6/12 - 1/10	Black	2 - SAE-Primary	7SAB152MG	37221	7SAB152MW	37222	No
12'	5/14 - 2/12	Black	2 - SAE-Primary	7MAB122MG	37173	7MAB122MW	37174	No
15'	5/14 - 2/12	Black	2 - SAE-Primary	7MAB152MG	37175	7MAB152MW	37176	No
15'	2/4	Red & Black	1 - Single / 1 - Dual	—	—	7CR152MW	37327	No
15'	2/4	Red & Black	2 - Dual Pole	—	—	7D152MW	37319	No
15'	1/4	Red	2 - Single Pole	—	—	7S152MW	37315	No
15'	2/4	Red & Black	2 - Single pole	—	—	7SD152MW	37323	No

Other configurations are available by special order. Contact the factory with your requirements.

